

STAR[®] S.O.S. SEALER[™]

Latex Based Oil Spot and Grease Contamination Primer/Sealer

GENERAL DESCRIPTION

STAR[®] S.O.S. SEALER[™] is a latex based coating/primer that adheres to, and seals, oil and grease spots on all types of asphalt pavements. The polymeric matrix and surfactants in STAR[®] S.O.S. SEALER[™] create a tough film that bonds aggressively to the contaminated area. STAR[®] S.O.S. SEALER[™] will allow both Asphalt Emulsion and Refined Tar sealers to bond properly these freshly primed areas. STAR[®] S.O.S. SEALER[™] will eliminate the need for excessive surface preparation that could damage the asphalt substrate.

OUTSTANDING PROPERTIES

- Will prevent oil and grease spots from bleeding up into the cured film of Asphalt Emulsion and Refined Tar sealers.
- Useful for areas that have been contaminated by tree sap, which causes sealcoatings to flake off in an unusual and confounding way.
- Is easy to use. Supplied as a concentrate with simple on-the-job mixing with water. Concentrated; allows easier storage and shipping.
- Applied by any conventional method; brush, spray, roller or squeegee.
- Dries in 20-30 minutes.
- Will not debond from the oil spot and will not allow the sealer to peel away from primed areas.
- Safe to store and easy water clean up.

RECOMMENDED USES

STAR[®] S.O.S. SEALER[™] is recommended on all asphalt surfaces where contamination and oil spotting problems need to be treated prior to sealcoating; parking lots, fast food restaurants, airports, gas stations, home driveways, schools, malls, etc.

MIX DESIGN RECOMMENDATIONS

STAR[®] S.O.S. SEALER[™] IS SUPPLIED AS A CONCENTRATE.

Dilution rate is; ONE part STAR[®] S.O.S. SEALER[™] with TWO parts clean potable water.

APPLICATION RATES

Must be applied to structurally sound pavements. Do not apply over chip seal or gilsonite sealed surfaces.

Apply Only One Coating of the diluted STAR[®] S.O.S. SEALER[™] over the contaminated area at the application rate of 450 - 500 Sq. Ft./Gal. (11.0 - 12.2 Sq. Meter/Liter). Concentrated STAR[®] S.O.S. SEALER[™] covers approximately 175 to 200 Sq. Ft./Gal.

APPLICATION TOOLS

- Use conventional tools; Brush, roller or low pressure sprayer.
- Clean up with water. Do not discard washings in the bodies of water or down sewer drains.
- Dried primer on tools - Wire brushing, scarping and peeling.
- Keep stored containers sealed tightly.

IMPORTANT WEATHER LIMITATIONS

- Surface and air temperature should be a min. 50° F (10° C) and rising.
- Do not apply on rainy, foggy, or extremely humid days, or when rain is in the forecast within 24 hours.

SURFACE PREPARATION

For best results remove all loose dirt and scrape off any heavy built up oil and grease. Hose off with clean water and let dry. Fresh oil drippings and contaminations must be washed with a detergent and then properly dried.

CURING TIME

Cure time will vary according to temperature and humidity at the time of application. Insufficiently cured films wear prematurely. Lower temperatures, high humidity and lack of direct sunlight will prolong the cure time. Higher temperatures, lower humidity and direct sunlight accelerate the cure process. STAR[®] S.O.S. SEALER[™] should dry in approximately 20-30 minutes in good drying conditions.

SPECIAL INSTRUCTIONS

Do not apply STAR[®] S.O.S. SEALER[™] in more than one coating. Multiple applications of STAR[®] S.O.S. SEALER[™] over the same spot could cause inter-coat adhesion failures.

CAUTIONS

KEEP FROM FREEZING / KEEP OUT OF REACH OF CHILDREN

Wear gloves and protective clothing. In case of contact, flush skin or eyes immediately with fresh water. If the product gets in the mouth or eyes see a physician immediately. Consult a Safety Data Sheet for details.

PACKAGING & AVAILABILITY

5-Gallon plastic pails, 55-gallon drums & 275-gallon plastic totes, and bulk at all STAR plant locations.

WARRANTY & DISCLAIMER The suggestions and related data contained on these pages are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. S.T.A.R., Inc. will not be responsible for any indirect or consequential damages. We will either replace or refund the purchase price in the event the products are proved to be defective, at our option.

