

<p style="text-align: center;">STAR PERMA-LINE TRAFFIC PAINT ALKYD BASED TRAFFIC & LINE MARKING PAINT Meets Fed. Std. TT-P-115 F and TT-P-85 E</p>
--

GENERAL DESCRIPTION

STAR PERMALINE is fast drying oil based traffic paint that is used for marking streets, airfields, highways, safety areas, etc. It is formulated with select resins and a blend of durable and light fast pigments.

OUTSTANDING FEATURES

Quick Drying
Solid hiding power
Long lasting
Bright and highly visible traffic markings
Ready to use. Easy to apply. No special modification to application equipment is required.

RECOMMENDED USES

STAR PERMALINE delivers excellent performance on both asphalt and concrete pavements and is recommended for ;
Highways, Streets, Parking Lots, Safety Areas, Curbs, etc.
Airfields, Runways, Aprons, etc.
Brick, Floors.

SPECIFICATIONS

Meets and or exceeds the requirements of Federal specifications;
TT-P-115 F- HIGHWAY AND TRAFFIC PAINT and
TT-P-85 E- AIRFIELD AND TRAFFIC MARKING PAINT

CONSTANTS AND PROPERTIES

Viscosity, Kus.	70- 75	Flash Point	32 F (Open cup)
Weight/Gallon, lb.	White 11.5 Yellow 11.5	Drying time:	
		To touch	10 mins.
Solids, % by Weight	White 71-75 Yellow 71-75	Trafficability	20 min.
Solids, % by Volume	White 49-51 Yellow 49-51	Film Thickness	Wet- 15 mils. Dry- 8 mils.
Dilution	None Required.	Coverage rate, lineal Ft.	2" wide-600-750 4" wide-300-375

APPLICATION

Do not use over uncured asphalt surfaces. New asphalt surfaces must be allowed to cure sufficiently to rid of the surface oils.

Surface Preparation-

1. General cleaning practices must be used to remove dirt, debris and old paint.
2. Oil and grease spots must be cleaned with detergent and sealed with STAR OIL SPOT PRIMER or STAR ONE STEP.
3. Concrete surfaces must be etched to create the right profile.

Method: Airless or conventional striping machines;

Conventional Spray: Use 0.1" tip size. Pressures may vary with ambient conditions.

Airless Spray: Typical tip orifice is 0.015 to 0.017 @ 1500-2000 psi air pressure.

Application: Thoroughly mix the contents in the container and apply on a properly prepared surface.

Temperatures: The ambient and surface temperatures must not be below 45 F.
Do not apply on damp surfaces or when rain is in the forecast.

Precautions: Read the material Safety Data Sheet, prior to use Yellow contains Lead.
Use only with adequate ventilation.
Avoid prolonged breathing of vapors or spray mist.
Avoid contact with eyes and skin.
Wear protective clothing and approved safety equipment.

First Aid: Skin Contact: Wash with soap and water.
Eyes: Flush with water for 15 minutes.
Swallowed: Get medical attention immediately.

DANGER

THIS CONTAINER MAY BE HAZARDOUS WHEN EMPTY- May contain explosive vapors or dangerous residue.

Do not cut, puncture or weld on or near the container.

KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES.

WARNING

FLAMMABLE

CONTAINS LEAD COMPOUND AND PETROLEUM DISTILLATES.
VAPORS MAY BE HARMFUL.

KEEP OUT OF REACH OF CHILDREN

FOR INDUSTRIAL USE ONLY.