



GENERAL DESCRIPTION

STAR-TRITON ushers a new generation of pavement sealcoatings that are high performance effective alternatives to both refined tar and asphalt emulsion sealers. STAR-TRITON is poised to reach the levels of prominence, as enjoyed by the entire family of STAR sealcoatings, for the protection, preservation and beautification of asphalt pavements.

Based on carefully selected grades of petroleum resins, minerals, specialty additives and performance boosters, STAR-TRITON® has an extraordinary degree of toughness and water repellency, unmatched by any competitive sealer. STAR-TRITON® forms a tough, durable and flexible coating that protects asphalt pavements from the damaging elements of weather, water penetration, de-icing salts, traffic damage, surface raveling/checking, gasoline and other petrochemicals. STAR-TRITON increases the life of your pavement by 300% or more, at 1/3 rd. the cost of new installations. The combination of state-of-the-art technology in manufacturing and raw material selection translates into the following:

OUTSTANDING PROPERTIES

Comparable to Refined Tar Sealers (RTS) in toughness, and overall durability.
Better than asphalt Emulsion Based Sealcoatings (AE) in resistance to fuel, salt and petrochemicals.
Color Stability- Similar to RTS, unlike AE, which have a tendency to fade with aging.
Expands the season i.e. early spring to late fall, significantly longer than AE sealers.
More Economical than AE-Allows higher dilution rates with water, in mix designs.
Water- based, easy to apply, handle and store.
Non-burning, non-irritating, with insignificant odor.
Beautifies While It Protects – Dries to an appealing dark charcoal color that enhances the value of the property. Snow removal becomes easier and traffic markings last longer.

RECOMMENDED USES

STAR-TRITON® is recommended for all asphalt pavements; home driveways, commercial parking lots, apartment complexes, restaurants, schools, gas stations, truck terminals, airfields/taxiways/airport shoulders, and many more.

QUALITY + PERFORMANCE + VALUE + INNOVATION + SERVICE

1150 Milepost Road | Columbus, OH 43228
Toll Free • 800.759.1912
Tel • 614.870.0744
Fax • 614.879.0598
www.starseal.com



APPLICATION

MIX DESIGN RECOMMENDATIONS

Important - All mix designs must include clean, quartz, angular sand.

	US	METRIC
STAR-TRITON®	100 Gal.	100 Liters
Water (Clean, Potable)	25-35 Gal.	25-35 Liters
Sand/Aggregate 50-70 AFS*	300-500 Lbs.	36-60 Kg.

* Crushed slag (i.e. Black Beauty) may be used as the aggregate, provided it is clean, angular and within 50-70 AFS gradation.

The use of an additive is optional, follow STAR's recommendations.

APPLICATION RATES

Must be applied to structurally sound pavements. Do not apply over chip seal or gilsonite sealed surfaces. The application rates shall be dictated by the traffic pattern and usage.

1 For Low to Medium Traffic Areas Apply Two (2) Coats:

a) Concentrated Sealer - the total coverage rate of 0.18 - 0.20 Gal./Sq. Yd. or 45 - 50 Sq. Ft./Gal. (1.1 - 1.22 Sq. Meter/Liter).

b) Mixed Sealer - 0.27 - 0.30 Gal./Sq. Yd. or 30 - 33 Sq. Ft./Gal. (0.73 - 0.81 Sq. Meter/Liter).

2 For High Traffic Areas Apply Three (3) Coats:

a) Concentrated Sealer - the total coverage rate of 0.25 - 0.28 Gal./Sq. Yd. or 32 - 36 Sq. Ft./Gal. (0.8 - 0.9 Sq. Meter/Liter).

b) Mixed Sealer - 0.38 - 0.42 Gal./Sq. Yd. or 21 - 24 Sq. Ft./Gal. (0.51 - 0.59 Sq. Meter/Liter).

QUALITY + PERFORMANCE + VALUE + INNOVATION + SERVICE

1150 Milepost Road | Columbus, OH 43228
Toll Free • 800.759.1912
Tel • 614.870.0744
Fax • 614.879.0598
www.starseal.com



IMPORTANT WEATHER CONSIDERATIONS & LIMITATIONS

- Surface and air temperature should be a min. 50° F (10° C) and rising.
- Do not apply on rainy, foggy, or extremely humid days, or when rain is in the forecast within 24 hours.
- If the pavement temperature is over 100° (38°C) dampen the pavement with a fine mist of water to facilitate even spreading. Do not allow water to puddle on the surface.

APPLICATION TOOLS

- Use conventional tools; Brush, rubber squeegee or spray rig.
- Clean up with Water. Do not discard washings in the bodies of water or down sewer drains.
- Dried sealer on tools - Wire brushing, scarping and peeling.
- Keep stored containers sealed tightly.

CURING TIME

Cure time will vary according to temperature and humidity at the time of application. Insufficiently cured films wear prematurely. Lower temperatures, high humidity and lack of direct sunlight will prolong the cure time. Higher temperatures, lower humidity and direct sunlight accelerate the cure process. If a second coat is to be applied, allow the first coat to dry sufficiently to withstand light vehicular and pedestrian traffic without damaging or scuffing the coating. After the application of the last coat, allow the coating to cure at least 20-24 hours under good drying conditions.

SPECIAL INSTRUCTIONS

Apply only on unsealed asphalt or surfaces previously sealed with either Asphalt Emulsion or Refined Tar based sealers. Do not apply over surfaces sealed with gilsonite and other solvent based seal coatings. New asphalt pavements must be allowed to cure at least 90 days in hot weather. Perform a water break free test to confirm that the surface oils have dissipated, by spreading water on the pavement. If the water does not bead, pavement is ready for seal-coating. Not recommended for steeply inclined surfaces, as they may become slippery when wet.

QUALITY + PERFORMANCE + VALUE + INNOVATION + SERVICE

1150 Milepost Road | Columbus, OH 43228
Toll Free • 800.759.1912
Tel • 614.870.0744
Fax • 614.879.0598
www.starseal.com



CAUTIONS

KEEP FROM FREEZING / KEEP OUT OF REACH OF CHILDREN/ Store in tightly closed containers.

Read Safety Data Sheet for details. Wear gloves and protective clothing. In case of contact, flush skin or eyes immediately with fresh water. If the product gets in the mouth or eyes see a physician immediately.

PACKAGING & AVAILABILITY

5-Gallon plastic pails, 55-gallon drums & 275-gallon plastic totes, and bulk at all STAR plant locations.

WARRANTY & DISCLAIMER Using additives not manufactured by S.T.A.R., Inc. may result in inconsistent or undesired results. STAR's additives are designed specifically for use with sealcoatings manufactured by STAR Member Plants. The suggestions and related data contained on these pages are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. S.T.A.R., Inc. will not be responsible for any indirect or consequential damages. We will either replace or refund the purchase price in the event the products are proved to be defective, at our option.

QUALITY + PERFORMANCE + VALUE + INNOVATION + SERVICE

1150 Milepost Road | Columbus, OH 43228
Toll Free • 800.759.1912
Tel • 614.870.0744
Fax • 614.879.0598
www.starseal.com