

STAR-SEAL PRO BLEND SAFETY DATA SHEET **PAGE 1 OF 18**

According to 190/2006/EC (REACH), 1272/2008/EC (CLP) and GHS

Printing Date 25.08.2014 Revision 25.08.2014

SECTION 1

IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 PRODUCT IDENTIFIER/TRADE NAME:

STAR-SEAL PRO BLEND

1.2 RELIVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST:

No further relevant information available.

Application of the Substance / the Mixture: Sealcoating for Pavements

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

Specialty Technology And Research, Incorporated (S.T.A.R., Inc.) Manufacturer/Supplier:

1150 Milepost Drive, Columbus, Ohio 43228

Tel: +1-614-870-0744 • Fax: +1-614-870-0598 • Toll Free +1-800-759-1912

Web Site: www.starseal.com

1.4 EMERGENCY TELEPHONE NUMBER:

ChemTel. Inc.

(800)255-3924, +1(813)248-0585

SECTION 2

HAZARDS IDENTIFICATION

2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

CLASSIFICATION ACCORDING TO REGULATION (EC) NO. 1272/2008

The following classifications are applicable only to the general GHS regulations and not the Specific CLP regulation: H360

The following hazard statements are applicable only to the EU regulations and not the US GHS regulation: H360FD, H400, H410

Repr. 1 H360: May damage fertility of the unborn child



Health Hazard

Muta. H340 May cause genetic defects. 1B

Carc. 1B H350 May cause cancer.

Repr. H360FD 1B May damage fertility. May damage the unborn child.



Environment

Aquatic Acute H400 Very toxic to aquatic life.

Aquatic Chronic 1 Very toxic to aquatic life with long lasting effects H410



Skin Sens. 1 H317 May cause an allergic skin reaction.

(Continued on page 2)

QUALITY A PERFORMANCE A VALUE A INNOVATION A SERVICE



1150 Milepost Road Columbus, Ohio 43228

800-759-1912 www.starseal.com

Tel 614-870-0744 Fax 614-870-0598



(Continued from page 1)

CLASSIFICATION ACCORDING TO DIRECTIVE 67/548/ECC or DIRECTIVE 1999/45/EC



T: Toxic

R45-46-60-61:

May cause cancer. May cause heritable genetic damage. May impair fertility.

May cause harm to the unborn child.



Xi: Sensitizina

May cause sensitization by skin contact.



N; Dangerous to the environment

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment..

Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

2.2 Label Elements

Labeling according to Regulation (EC) No 1272/2008

The product is classified and labeled according to the CLP regulation.

Hazard pictograms



This pictogram only applicable for EU regulations. Not for use in the United States (OSHA GHS).







GHS07 GHS08 GHS09

Signal word Danger

Hazard-determining components of labelling:

Pitch, coal tar, high-temp. benzo[a]pyrene chrysene Dibenzo(a,h)pyrene

Hazard statements

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H360FD, H410.

The following Hazard Statements are applicable only to the general GHS regulations and not the specific CLP regulation: H360.

(Continued on page 3)















(Continued from page 2)

H360	May damage fertility or the unborn child.
H317	May cause an allergic skin reaction.
11240	May acres gonetic defeate

May cause genetic defects. H340

H350 May cause cancer.

May damage fertility. May damage the unborn child. H360FD Very toxic to aquatic life with long lasting effects. H410

Precautionary statements

P261 Avoid breathing mist/vapors/spray.

P281 Use personal protective equipment as required.

P202 Do not handle until all safety precautions have been read and understood.

IF exposed or concerned: Get medical advice/attention. P308+P313 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P302+P352 IF ON SKIN: Wash with plenty of water.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

Restricted to professional users.

Hazard description:

WHMIS-symbols:

D2A - Very toxic material causing other toxic effects



NFPA ratings (Scale 0-4)



Health = 2

Fire = 0

Reactivity = 0

HMIS ratings (Scale 0-4)



Health = *2

Fire = 0

Reactivity = 0

* - Indicates a long term health hazard from repeated or prolonged exposures.

HMIS Long Term Health Hazard Substances

14808-60-7 quartz		
91-20-3	naphthalene	
50-32-8	benzo[a]pyrene	
65996-93-2 Pitch, coal tar, high-temp		

(Continued on page 4)













(Continued from page 3)

2.3 Other Hazards

Results of PBT and vPvB assessment

PBT

65996-93-2 Pitch, coal tar, high-temp.

vPvB: Not applicable.

SECTION 3

COMPOSITION / INFORMATION ON INGREDIENTS

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions

Dangerous components:

CAS: 65996-93-2	Pitch, coal tar, high-temp.	20-30%
EINECS: 266-028-2	PBT	
Index number: 648-055-00-5	T Carc. Cat. 2 R45	
	♦ Carc. 1B, H350	
CAS: 1332-58-7	Kaolin	15-20%
EC number: 310-194-1	substance with a Community workplace exposure limit	
CAS: 14808-60-7	quartz	3-7%
	substance with a Community workplace exposure limit	
CAS: 206-44-0	fluoranthene	0.5-1.5%
EINECS: 205-912-4	Xn R20;	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	Acute Tox. 4, H302	
CAS: 91-20-3	naphthalene	0.5-1.5%
EINECS: 202-049-5	Xn R22-40;	
Index number: 601-052-00-2	Carc. Cat. 3	
	© Carc. 2, H351	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	Acute Tox. 4, H302	
CAS: 56-55-3	benz[a]anthracene	0.1-1%
EINECS: 200-280-6	■ T Carc. Cat. 2 R45;	
Index number: 601-033-00-9	© Carc. 1B, H350	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 218-01-9	chrysene	0.1-1%
EINECS: 205-923-4 Index number: 601-048-00-0	☑ T Carc. Cat. 2 R45; 🔀 Xn R68; 💆 N R50/53 Muta. Cat. 3	
	♦ Muta. 2, H341; Carc. 1B, H350	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

(Continued on page 5)













(Continued from page 4)

CAS: 50-32-8 EINECS: 200-028-5 Index number: 601-032-00-3	benzo[a]pyrene ■ T Carc. Cat. 2, Muta. Cat. 2, Repr. Cat. 2 R45-46-60-61; ■ Xi R43; ■ N R50/53 ■ Muta. 1B, H340; Carc. 1B, H350; Repr. 1B, H360FD ■ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 • Skin Sens. 1, H317	0.1-1%
CAS: 193-39-5 EINECS: 205-893-2	indeno[1,2,3-cd]pyrene ♣ Carc. 2, H351	0.1-1%
CAS: 205-82-3 EINECS: 205-910-3 Index number: 601-035-00-X	benzo[j]fluoranthene ☐ T Carc. Cat. 2 R45; N R50/53 Carc. 1B, H350 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	0.1-1%
CAS: 189-64-0	dibenzo(a,h)pyrene	0.1-1%
EINECS: 205-878-0	◆Muta. 2, H341; Carc. 1B, H350; STOT RE 2, H373	
CAS: 207-08-9 EINECS: 205-916-6 Index number: 601-036-00-5	benzo[k]fluoranthene ☐ T Carc. Cat. 2 R45; N R50/53 Carc. 1B, H350 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	0.1-1%
CAS: 189-55-9	dibenzo(a,i)pyrene Carc. 2, H351	0.1-1%
CAS: Proprietary EINECS: Proprietary	alkoxylated fatty amines C R34; Xn R22 Skin Corr. 1B, H314; Eye Dam. 1, H318 Aquatic Acute 1, H400 Acute Tox. 4, H302; Skin Sens. 1, H317	0.1-1%

SVHC

65996-93-2 Pitch, coal tar, high-temp.

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4

FIRST AID MEASURES

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

After skin contact:

Do not pull solidified product off the skin.

Immediately wash with water and soap and rinse thoroughly.

Remove any clothing soiled by the product.

If skin irritation continues, consult a doctor.

(Continued on page 6)













(Continued from page 5)

After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

Slight irritant effect on skin and mucous membranes.

Slight irritant effect on eyes.

Gastric or intestinal disorders.

Hazards

Carcinogenic.

May damage fertility or the unborn child.

Possible risk of irreversible effects.

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

May produce a nephrotoxic / hepatotoxic effect.

Contains benzo[a]pyrene. May produce an allergic reaction.

SECTION 5

FIRE FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents: Water

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information No further relevant information available

SECTION 6

ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Particular danger of slipping on leaked/spilled product.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

(Continued on page 7)









(Continued from page 6)

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Pick up mechanically.

Dispose contaminated material as waste according to item 13.

Send for recovery or disposal in suitable receptacles.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7

HANDLING AND STORAGE

7.1 Precautions for safe handling

Use only in well ventilated areas.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about fire - and explosion protection: Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

Do not store together with acids.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from frost.

7.3 Specific end use(s) No further relevant information available.

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:			
65996-93-2 Pitc	65996-93-2 Pitch, coal tar, high-temp.		
PEL (USA)	Long-term value: 0.2 mg/m³		
REL (USA)	Long-term value: 0.1* mg/m³ *Cyclohexane-extrble. fraction; Pocket Guide Apps. A+C		
TLV (USA)	Long-term value: 0.2 mg/m³ BEIp		
EL (Canada)	Long-term value: 0.2 mg/m³ soluble aerosol; ACGIH A1; IARC 1		
EV (Canada)	Long-term value: 0.2 mg/m³ as total benzene-soluble compounds		

(Continued on page 8)












(Continued from page 7)

1332-58-7 Kaolin		
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction	
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction	
TLV (USA)	Long-term value: 2* mg/m³ E; as respirable fraction	
EL (Canada)	Long-term value: 2 mg/m³	
EV (Canada)	Long-term value: 2(D) mg/m³ respirable	
14808-60-7 qua	rtz	
PEL(USA) REL (USA)	see Quartz listing Long-term value: 0.05* mg/m³ *respirable dust; See Pocket Guide App. A	
TLV (USA)	Long-term value: 0.025* mg/m³ *as respirable fraction	
EL (Canada)	Long-term value: 0.025 mg/m³ ACGIH A2; IARC 1	
EV (Canada)	Long-term value: 0.10* mg/m³ *respirable fraction	
91-20-3 naphth	alene	
IOELV (EU)	Long-term value: 30 mg/m³, 10 ppm	
PEL (USA)	Long-term value: 50 mg/m³, 10 ppm	
REL (USA)	Short-term value: 75 mg/m³, 15 ppm Long-term value: 50 mg/m³, 10 ppm	
TLV (USA)	Long-term value: 52 mg/m³, 10 ppm Skin; BEI	
EL (Canada)	Short-term value: 15 ppm Long-term value: 10 ppm Skin; IARC 2B	
EV (Canada)	Short-term value: 78 mg/m³, 15 ppm Long-term value: 52 mg/m³, 10 ppm	
56-55-3 benz[a]anthracene		
TLV (USA)	L; BEIp	
EL (Canada)	ACGIH A2; IARC 2B	
218-01-9 chrys		
PEL (USA)	Long-term value: 0.2 mg/m³ see Coal Tar Pitch Volatiles	
REL (USA)	Long-term value: 0.1* mg/m³ *Cyclohexane-extrble. fraction; Pocket Guide Apps. A+C	
TLV (USA)	L, BEIp	
EL (Canada)	IARC 2B	

(Continued on page 9)













(Continued from page 8)

50-32-8 benzo[a]pyrene

PEL (USA) Long-term value: 0.2 mg/m3

see Coal tar pitch volatiles

Long-term value: 0.1 mg/m³ REL (USA)

Coal tar pitch volatile; Pocket Guide Apps. A+C

TLV (USA) L: BEIp

ACGIH A2; IARC 1 EL (Canada)

DNELs No further relevant information available. PNECs No further relevant information available.

Ingredients with biological limit values:

65996-93-2 Pitch, coal tar, high-temp.

BEI (USA)

Medium: urine

Time: end of shift at end of workweek

Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)

56-55-3 benz[a]anthracene

BEI (USA)

Medium: urine

Time: end of shift at end of workweek

Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)

218-01-9 chrysene

BEI (USA)

Medium: urine

Time: end of shift at end of workweek

Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)

50-32-8 benzo[a]pyrene

BEI (USA)

Medium: urine

Time: end of shift at end of workweek

Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

Respiratory protection:

Not required under normal conditions of use.

Use suitable respiratory protective device when aerosol or mist is formed.

Use suitable respiratory protective device in case of insufficient ventilation.

For spills, respiratory protection may be advisable.

(Continued on page 10)











(Continued from page 9)

Protection of hands:

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Safety glasses



Body protection:

Protective work clothing

Limitation and supervision of exposure into the environment

No further relevant information available.

Risk management measures

See Section 7 for additional information.

8.3 Other Information: No further relevant information available.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

General Information:

Δn	nas	ran	CO.
Λh	hea	Iaii	ce:

Form......Heavy Bodied Semi-Fluid Liquid

Color Dark Chocolate Brown

Change in Condition:

Melting point/Melting RangeNot Determined Boiling point/Boiling rangeUndetermined Flash Point......Not Applicable Flammability (Solid Gaseous)......Not Applicable Auto/Self-Ignition TemperatureNot determined **Decomposition Temperature**Not determined

(Continued on page 11)













(Continued from page 10)

Self-IgnitingProduct is not self-igniting.

Danger of Explosion Product does not present an explosion Hazard.

Explosion Limits:

LowerNot determined UpperNot determined Vapor PressureNot determined **Density at 20° C**......1.20 – 1.25 g/cm³ Relative DensityNot Determined Vapor Density......Not Determined Evaporation RateNot Determined

Solubility in/Miscibility with Water Dilutable with water Partition Coefficient (n-octanol/water) Not Determined

Viscosity:

DynamicNot Determined KinematicNot Determined

9.2 Other Information: No further relevant information available

SECTION 10

STABILITY AND REACTIVITY

10.1 Reactivity

10.2 Chemical stability

Thermal decomposition/conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Reacts with strong oxidizing agents.

Reacts with strong acids.

10.4 Conditions to avoid: Store away from oxidizing agents.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11

TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:		
206-44-0 fluoranthene		
	Oral LD50 2000 mg/kg (rat) Dermal LD50 3180 mg/kg (rabbit)	
91-20-3 naphthalene		

(Continued on page 12)

Dermal LD50

LD50

490 mg/kg (rat) 5000 mg/kg (rat)







Oral



(Continued from page 11)

Primary irritant effect:

On the skin: Slight irritant effect on skin and mucous membranes.

On the eye: Slight irritant effect on eyes.

Sensitization: Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Danger through skin adsorption.

The product can cause inheritable damage.

Toxic and/or corrosive effects may be delayed up to 24 hours.

May cause genetic defects.

May cause cancer.

May damage fertility or the unborn child.

Sensitization: Sensitization possible by skin contact.

Repeated dose toxicity:

May cause damage to organs through prolonged or repeated exposure. Repeated exposures may result in skin and/or respiratory sensitivity.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):

Muta. 1B, Carc. 1B, Repr. 1B

SECTION 12

ECOLOGICAL INFORMATION

12.1 Toxicity

Aquatic toxicity:

Toxic for aquatic organisms

206-44-0 fluoranthene

0.0077 mg/l (Oncorhynchus mykiss) (96h)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxical effects:

Remark:

Very toxic for fish

The product is oxygen-consuming. The declared action may be partly caused by lack of oxygen.

Due to mechanical actions of the product (e.g. agglutinations) damages may occur.

Additional ecological information:

General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

12.5 Results of PBT and vPvB assessment

PBT:

65996-93-2 Pitch, coal tar, high-temp.

(Continued on page 13)









800-759-1912 www.starseal.com



(Continued from page 12)

vPvB: Not applicable.

12.6 Other adverse effects: No further relevant information available.

SECTION 13

DISPOSAL CONSIDERATION

13.1 Waste treatment methods

Recommendation:

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

SECTION 14

TRANSPORTATION INFORMATION

14.1 UN-Number DOT

UN3082

Classification as a MARINE POLLUTANT is based on MARPOL and DOT rules. Labeling as a MARINE POLLUTANT is not required for non-bulk single package shipments by motor vehicle, rail car or aircraft. Bulk packaging consists of a maximum capacity of greater than 450L (119 gallons) for a liquid and a maximum net mass greater than 400kg (882 pounds) for a solid.

UN3082

ADR, IMDG, IATA

14.2 UN proper shipping name

DOT

ADR

IMDG

IATA

Environmentally hazardous substances, liquid, n.o.s.

(Naphthalene, crude, fluoranthene)

3082 ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, LIQUID, N.O.S. (NAPHTHALENE,

CRUDE, fluoranthene)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

LIQUID, N.O.S. (NAPHTHALENE, CRUDE,

fluoranthene), MARINE POLLUTANT

ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

LIQUID, N.O.S. (NAPHTHALENE, CRUDE,

fluoranthene)

(Continued on page 14)

QUALITY A PERFORMANCE A VALUE A INNOVATION A





STAR-SEAL PRO BLEND SAFETY DATA SHEET **PAGE 14 OF 18**

(Continued from page 13)

14.3 Transport hazard class(es)

DOT, IMDG, IATA



Class 9 Miscellaneous dangerous substances and articles.

Label **ADR**



Special marking (ADR):

Class 9 (M6) Miscellaneous dangerous substances and

articles.

Label 9

14.4 Packing group

DOT, ADR, IMDG, IATA Ш

14.5 Environmental hazards: Product contains environmentally hazardous

substances: benz[a]anthracene

Marine pollutant: Yes

> Symbol (fish and tree) Symbol (fish and tree)

Symbol (fish and tree) Special marking (IATA):

14.6 Special precautions for user: Warning: Miscellaneous dangerous substances and

articles.

Danger code (Kemler): 90 **EMS Number:** F-A.S-F

14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Transport category 3 **Tunnel restriction code** Ε

IMDG

Limited quantities (LQ) 5I

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml UN 3082, ENVIRONMENTALLY HAZARDOUS

UN "Model Regulation": SUBSTANCE, LIQUID, N.O.S. (NAPHTHALENE,

CRUDE, fluoranthene), 9, III

(Continued on page 15)











(Continued from page 14)

SECTION 15

REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture **United States (USA) SARA**

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313	Section 313 (Specific toxic chemical listings):		
206-44-0	fluoranthene		
91-20-3	naphthalene		
56-55-3	benz[a]anthracene		
218-01-9	chrysene		
50-32-8	benzo[a]pyrene		
193-39-5	indeno[1,2,3-cd]pyrene		
205-82-3	benzo[j]fluoranthene		
189-64-0	Dibenzo(a,h)pyrene		
207-08-9	benzo[k]fluoranthene		
189-55-9	Dibenzo(a,i)pyrene		

TSCA (Toxic Substances Control Act):

All ingredients are listed.

Proposition 65 (California):

Chemicals known to cause cancer:

Reference to Crystalline Silica and/or Quartz is based on unbound respirable particles and is not generally applicable to product as supplied.

14808-60-7	quartz
91-20-3	naphthalene
56-55-3	benz[a]anthracene
218-01-9	chrysene
50-32-8	benzo[a]pyrene
193-39-5	indeno[1,2,3-cd]pyrene
205-82-3	benzo[j]fluoranthene
189-64-0	Dibenzo(a,h)pyrene
207-08-9	benzo[k]fluoranthene
189-55-9	Dibenzo(a,i)pyrene

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

(Continued on page 16)

QUALITY A PERFORMANCE A VALUE A INNOVATION A







(Continued from page 15)

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenic Categories

EPA (Enviro	EPA (Environmental Protection Agency)		
206-44-0	fluoranthene	D	
91-20-3	naphthalene	C, CBD	
56-55-3	benz[a]anthracene	B2	
218-01-9	chrysene	B2	
50-32-8	benzo[a]pyrene	B2	
193-39-5	indeno[1,2,3-cd]pyrene	B2	
207-08-9	benzo[k]fluoranthene	B2	

IARC (Interna	tional Agency for Research on Ca	ancer)	
65996-93-2	Pitch, coal tar, high-temp.	1	
14808-60-7	quartz	1	
206-44-0	fluoranthene	3	
91-20-3	naphthalene	2B	
56-55-3	benz[a]anthracene	2B	
218-01-9	chrysene	2B	
50-32-8	benzo[a]pyrene	1	
193-39-5	indeno[1,2,3-cd]pyrene	2B	
205-82-3	benzo[j]fluoranthene	2B	
189-64-0	Dibenzo(a,h)pyrene	2B	
207-08-9	benzo[k]fluoranthene	2B	
189-55-9	Dibenzo(a,i)pyrene	2B	

TLV (Threshold Limit Value established by ACGIH)			
65996-93-2	Pitch, coal tar, high-temp.	A1	
1332-58-7	Kaolin	A4	
14808-60-7	quartz	A2	
91-20-3	naphthalene	A4	
56-55-3	benz[a]anthracene	A2	
218-01-9	chrysene	A3	
50-32-8	benzo[a]pyrene	A2	

NIOSH-Ca (National Institute for Occupational Safety and Health)	
65996-93-2	Pitch, coal tar, high-temp.
14808-60-7	quartz
218-01-9	chrysene
50-32-8	benzo[a]pyrene

(Continued on page 17)













(Continued from page 16)

Canada

Canadian Domestic Substances List (DSL)	
All ingredients are listed.	

Canadian Ingredient Disclosure list (limit 0.1%)	
65996-93-2	Pitch, coal tar, high-temp.
56-55-3	benz[a]anthracene
218-01-9	chrysene
50-32-8	benzo[a]pyrene
193-39-5	indeno[1,2,3-cd]pyrene
189-64-0	Dibenzo(a,h)pyrene
189-55-9	Dibenzo(a,i)pyrene

Canadian Ingredient Disclosure list (limit 1%)	
14808-60-7	quartz
206-44-0	fluoranthene
91-20-3	naphthalene

Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

Other regulations, limitations and prohibitive regulations

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Substances of very high concern (SVHC) according to REACH, Article 57
65996-93-2 Pitch, coal tar, high-temp.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16

OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

•	io vanit prina	
	H302	Harmful if swallowed.
	H314	Causes severe skin burns and eye damage.
	H317	May cause an allergic skin reaction.
	H318	Causes serious eye damage.
	H340	May cause genetic defects.
	H341	Suspected of causing genetic defects.
	H350	May cause cancer.
	H351	Suspected of causing cancer.
	H360FD	May damage fertility. May damage the unborn child.
	H373	May cause damage to organs through prolonged or repeated exposure.
	H400	Very toxic to aquatic life.
	H410	Very toxic to aquatic life with long lasting effects.

(Continued on page 18)











(Continued from page 17)

R20 Harmful by inhalation. Harmful if swallowed. R22

R34 Causes burns.

R40 Limited evidence of a carcinogenic effect. May cause sensitization by skin contact. R43

May cause cancer. R45

May cause heritable genetic damage. R46

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R50/53

May impair fertility. R60

May cause harm to the unborn child. R61 R68 Possible risk of irreversible effects.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

International Maritime Code for Dangerous Goods IMDG: DOT: US Department of Transportation

International Air Transport Association IATA:

Globally Harmonized System of Classification and Labeling of Chemicals GHS:

American Conference of Governmental Industrial Hygienists ACGIH: European Inventory of Existing Commercial Chemical Substances **EINECS:**

European List of Notified Chemical Substances **ELINCS**:

Chemical Abstracts Service (division of the American Chemical Society) CAS:

NFPA: National Fire Protection Association (USA) Hazardous Materials Identification System (USA) HMIS:

Workplace Hazardous Materials Information System (Canada) WHMIS:

Derived No-Effect Level (REACH) DNEL:

Predicted No-Effect Concentration (REACH) PNEC:

Lethal concentration, 50 percent LC50:

Lethal dose, 50 percent LD50:

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitization - Skin, Hazard Category 1 Muta. 1B: Germ cell mutagenicity, Hazard Category 1B Germ cell mutagenicity, Hazard Category 2 Muta. 2: Carcinogenicity, Hazard Category 1B Carc. 1B: Carc. 2: Carcinogenicity, Hazard Category 2 Reproductive toxicity, Hazard Category 1B Repr. 1B:

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2 Hazardous to the aquatic environment - Acute Hazard, Category 1 Aquatic Acute 1: Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com

- END OF SDS -







800-759-1912