

# According to 190/2006/EC (REACH), 1272/2008/EC (CLP) and GHS

 
 Printing Date 10.06.2022
 Revision 10.06.2022

 SECTION 1
 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/ UNDERTAKING

- 1.1 PRODUCT IDENTIFIER/TRADE NAME: STAR-LTCA
- 1.2 RELIVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST: No further relevant information available. Application of the Substance / the Mixture: Low Temperature Cure Additive for Sealcoatings
- **1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:** 

   Manufacturer/Supplier:
   Specialty Technology And Research, Incorporated (S.T.A.R., Inc.)

   1150 Milepost Drive, Columbus, Ohio 43228

   Tel: +1-614-870-0744 Fax: +1-614-870-0598 Toll Free +1-800-759-1912

   Web Site: www.starseal.com
- 1.4 EMERGENCY TELEPHONE NUMBER: ChemTel, Inc. (800)255-3924, +1(813)248-0585

**SECTION 2** 

HAZARDS IDENTIFICATION

## 2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

ACUTE ORAL TOXICITY FLAMMABLE LIQUIDS EYE IRRITATION SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) SPECIFIC TARGET ORGAN TOXICITY - (REPEATED EXPOSURE) Target Organs - Kidney, Liver. Category 4 Category 2 Category 2A Category 3 Category 2

2.2 Label Elements

Hazard Pictograms:



Hazard statements Harmful if swallowed. May form explosive mixtures with air. Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

QUALITY 🔺 PERFORMANCE 🔺 VALUE 🔺 INNOVATION 🔺 SERVICE

1150 Milepost Road Columbus, Ohio 43228 800-759-1912 www.starseal.com



#### **Precautionary statements:**

Avoid release to environment.

Avoid breathing mist/vapors/spray.

Use personal protective equipment as required.

Do not handle until all safety precautions have been read and understood.

If exposed or concerned: Get medical advice/attention.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin well with water/shower. IF SWALLOWED, rinse mouth. DO NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell

In case of fire: Use for extinction: CO2, Powder. Do not use water.

Store in a well-ventilated place. Keep containers tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

## **SECTION 3**

# **COMPOSITION / INFORMATION ON INGREDIENTS**

3.1 Substance- Not applicable

3.2 Mixtures Proprietary

#### Additional information:

The identity of the ingredient(s) and/or exact percentage(s) are being withheld as a trade secret.

For the wording of the listed risk phrases refer to section 16.

# SECTION 4

FIRST AID MEASURES

## 4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

## After inhalation:

Supply fresh air; consult doctor in case of complaints. Provide oxygen treatment if affected person has difficulty breathing. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation

## After skin contact:

Immediately wash with water and soap and rinse thoroughly. Remove any clothing soiled by the product. If skin irritation continues, consult a doctor.

## After eye contact:

Remove contact lenses if worn. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

## After swallowing:

Rinse out mouth and then drink plenty of water. Do not induce vomiting; call for medical help immediately.

## 4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions Serious irritant effect on skin. Can cause frostbite. Serious irritant effect on eyes. Can cause Central Nervous System (CNS) depression.

QUALITY A PERFORMANCE A VALUE A INNOVATION A SERVICE



#### **4.3 Indication of any immediate medical attention and special treatment needed** If swallowed, gastric irrigation with added, difficulty in breathing.

# SECTION 5

FIRE FIGHTING MEASURES

## 5.1 Extinguishing media

Suitable extinguishing agents: CO2, Dry Chemical, Water spray (fog), Alcohol-resistant foam.

For safety reasons unsuitable extinguishing agents: Do not use water jet.

#### 5.2 Special hazards arising from the substance or mixture

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

#### 5.3 Advice for firefighters

#### **Protective equipment:**

Wear self-contained respiratory protective device. Wear fully protective suit.

Additional information No further relevant information available

# **SECTION 6**

# ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation.

No flares, smoking or flames in hazard area.

Particular danger of slipping on leaked/spilled product.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

#### 6.2 Environmental precautions:

Do not allow to enter soil, sewers/ surface or ground water. Inform respective authorities in case of seepage into water course or sewage system.

# 6.3 Methods and material for containment and cleaning up:

Absorb with inert dry material (sand, earth, vermiculite or diatomaceous earth) and place it in an appropriate waste disposal container. Dispose contaminated material as waste according to item 13.

Send for recovery or disposal in suitable receptacles.

## 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

# **SECTION 7**

## HANDLING AND STORAGE

## 7.1 Precautions for safe handling

Use personal protective equipment as required. Use only non-sparking tools. Do not breathe mist/vapors/spray. Avoid contact with eyes, skin and clothing. Do not ingest. Use only in well ventilated areas. Open and handle receptacle with care.

Open and nancie receptacle with ca

# QUALITY 🔺 PERFORMANCE 🔺 VALUE 🔺 INNOVATION 🔺 SERVICE

1150 Milepost Road Columbus, Ohio 43228 800-759-1912 www.starseal.com



Information about fire - and explosion protection: Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

**Requirements to be met by storerooms and receptacles:** Keep out of the reach of children. Keep in tightly closed and sealed containers.

#### Information about storage in one common storage facility:

Store away from food and drinks.

Store away from oxidizing agents, strong acids, strong bases, and aldehydes. Store away from heat, sparks or flames.

#### Further information about storage conditions:

Store in cool, dry conditions in well-sealed receptacles.

#### 7.3 Specific end use(s) No further relevant information available.

# **SECTION 8**

**EXPOSURE CONTROLS / PERSONAL PROTECTION** 

#### 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

67-63-0 Isopropyl Alcohol	
ACGIH TLV (USA)	TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes
OSHA PEL (USA)	TWA: 400 ppm or 980 mg/m <sup>3</sup> 8 hours
	STEL: 500 ppm or 1225 mg/m <sup>3</sup> 15 minutes
NIOSH REL (USA)	TWA: 400 ppm or 980 mg/m <sup>3</sup> 10 hours
	STEL: 500 ppm or 1225 mg/m <sup>3</sup> 15 minutes

## 107-21-1 Ethylene Glycol

ACGIH TLV	TWA: 25 ppm	
	STEL: 50 ppm or 10 mg/m <sup>3</sup>	
OSHA PEL	(Vacated) Ceiling: 50 ppm (Vacated) Ceiling: 125 mg/m³	
OEL (MEXICO)	TWA ceiling: 100 mg/m³	

## 8.2 Exposure controls

## Personal protective equipment:

#### General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food and drinks.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

#### **Respiratory protection:**

Not required under normal conditions of use.

Use suitable respiratory protective device when aerosol or mist is formed.

Use suitable respiratory protective device in case of insufficient ventilation.

For spills, respiratory protection may be advisable.

# QUALITY A PERFORMANCE A VALUE A INNOVATION A SERVICE



## **Protection of hands:**

Protective gloves



The glove material must be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time must be found out by the manufacturer of the protective gloves and has to be observed.

## Eye protection:

Safety glasses



Body protection:

Protective work clothing

#### Limitation and supervision of exposure into the environment

No further relevant information available.

#### **Risk management measures**

See Section 7 for additional information.

# **8.3 Other Information:** No further relevant information available.

## **SECTION 9**

PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

#### **General Information:**

Appearance:	
Form	Liquid
Color	Colorless
Odor	Alcohol like
Odor Threshold	Not determined
pH Value	Not determined
Change in Condition: Melting point/Melting Range Boiling point/Boiling range	
Flash Point	Not Determined
Flammability (Solid Gaseous)	Not Applicable
Auto/Self-Ignition Temperature	Not determined
Decomposition Temperature	Not determined
Self-Igniting	Product is not self-igniting.

QUALITY A PERFORMANCE A VALUE A INNOVATION A SERVICE



#### **Explosion Limits:**

Lower Upper	
Vapor Pressure	Not determined
Density at 20° C	. 0.94 – 0.96 g/cm <sup>3</sup>
Relative Density	Not Determined
Vapor Density	Not Determined
Evaporation Rate	Not Determined
Solubility in/Miscibility with Water	Dilutable with water
Partition Coefficient (n-octanol/water)	Not Determined
Viscosity:	
Dynamic	
Kinematic	Not Determined

9.2 Other Information: No further relevant information available

# **SECTION 10**

# STABILITY AND REACTIVITY

# 10.1 Reactivity

None Known.

10.2 Chemical stability

## Thermal decomposition/conditions to be avoided:

No decomposition if used and stored according to specifications.

# 10.3 Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

- 10.4 Conditions to avoid: Avoid sources of ignition. Avoid heat. Avoid incompatible products.
- 10.5 Incompatible materials: Strong oxidizing agents, Strong acids, Strong bases, Aldehydes
- 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTI	ON 11

TOXICOLOGICAL INFORMATION

# **11.1 Information on toxicological effects**

Acute toxicity:

## 67-63-0 Isopropyl Alcohol

Oral LD50 5000 mg/kg (rat) Dermal LD50 12800 mg/kg (rabbit)		
Dermal LD50 12800 mg/kg (rabbit)	Oral	LD50 5000 mg/kg (rat)
	Dermal	LD50 12800 mg/kg (rabbit)
Inhalation Gas LC50 45248 ppm (rat)	Inhalation Gas	LC50 45248 ppm (rat)

107-21-1 Ethyle	ene Glycol
Oral	LD50 7712 mg/kg (rat)
Dermal	LD50 9530 µL/kg (rabbit) 10600 mg/Kg (rat) >3500 mg/Kg (mice)
Inhalation Gas	LC50 > 2.5 mg/L (rat)

# Primary irritant effect:

**On the skin:** Slight irritant effect on skin and mucous membranes. **On the eye:** Slight irritant effect on eyes.

Sensitization: Sensitization possible through skin contact.

# QUALITY A PERFORMANCE A VALUE A INNOVATION A SERVICE

1150 Milepost Road Columbus, Ohio 43228 800-759-1912 www.starseal.com



#### Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Can cause central nervous system (CNS) depression.

May cause drowsiness or dizziness.

May cause respiratory tract irritation.

Sensitization: Sensitization possible by skin contact.

#### Repeated dose toxicity:

May cause damage to organs through prolonged or repeated exposure. Repeated exposures may result in skin and/or respiratory sensitivity.

# **SECTION 12**

# **ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Aquatic toxicity: Toxic for aquatic organisms.

- 12.2 Persistence and degradability-
- 12.3 Bio-accumulative potential-

12.4 Mobility in soil-

12.5 Results of PBT and vPvB assessment-

12.6 Other adverse effects:

No further relevant information available. No further relevant information available. No further relevant information available. None available No further relevant information available.

## **SECTION 13**

## DISPOSAL CONSIDERATION

# 13.1 Waste treatment methods

## **Recommendation:**

Must not be disposed together with household garbage. Disposal of this product, solutions and any byproducts should always comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

#### Uncleaned packaging:

## Recommendation:

Disposal must be made according to official regulations.

## SECTION 14

# TRANSPORTATION INFORMATION

In accordance with DOT. 14.1 UN-Number 14.2 UN proper shipping name 14.3 Additional Information Special Transport Precaution-

Not Applicable. Not Applicable None available Read all safety precautions before handling the product.

QUALITY A PERFORMANCE A VALUE A INNOVATION A SERVICE

800-759-1912 www.starseal.com



# SECTION 15

# REGULATORY INFORMATION

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture United States (USA) SARA

#### Section 313 (Specific toxic chemical listings):

		<b>C</b> ;
107-21-1	Ethylene Glycol	
67-63-0	Isopropyl Alcohol	

## **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

#### Proposition 65 (California):

Chemicals known to cause cancer:

Not applicable.

## Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

## Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

## Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

# SECTION 16

# **OTHER INFORMATION**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## Relevant phrases

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- R20 Harmful by inhalation.
- R22 Harmful if swallowed.
- R43 May cause sensitization by skin contact.
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labeling of Chemicals
- ACGIH: American Conference of Governmental Industrial Hygienists
- QUALITY A PERFORMANCE A VALUE A INNOVATION A SERVICE



EINECS:	European Inventory of Existing Commercial Chemical Substances
ELINCS:	European List of Notified Chemical Substances
CAS:	Chemical Abstracts Service (division of the American Chemical Society)
NFPA:	National Fire Protection Association (USA)
HMIS:	Hazardous Materials Identification System (USA)
WHMIS:	Workplace Hazardous Materials Information System (Canada)
DNEL:	Derived No-Effect Level (REACH)
PNEC:	Predicted No-Effect Concentration (REACH)
LC50:	Lethal concentration, 50 percent
LD50:	Lethal dose, 50 percent
Acute Tox. 4:	Acute toxicity, Hazard Category 4
Skin Corr. 1B:	Skin corrosion/irritation, Hazard Category 1B
Eye Dam. 1:	Serious eye damage/eye irritation, Hazard Category 1
Skin Sens. 1:	Sensitization - Skin, Hazard Category 1
STOT RE 2:	Specific target organ toxicity - Repeated exposure, Hazard Category 2
Aquatic Acute 1:	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1:	Hazardous to the aquatic environment - Chronic Hazard, Category 1

#### Sources

SDS Prepared by:	STAR, INC., 1150 Milepost Drive, Columbus, OH 43026 Tel. no. 614-870-0744, fax 614-870-0598 Website: <u>www.starseal.com</u>
Date of Preparation	October 06, 2022
Date of Issue	October 06, 2022.

- END OF SDS -

